



Deploying AirCatch settings using Apple Configurator or MDM solutions

AirCatch settings can be deployed using the Apple Configurator or third party MDM solutions that allow configuring of Mail and Contacts settings.

Settings can be one of three types

Description – can be set to any value

Fixed – Cannot be changed

Set in Configurator – Values are set in the Advanced Settings tab on the AirCatch configurator. If changed then the values show below should be changed to match the amended settings. In most situations you will not need to change any of these values

The following settings are required for Mail.

Key	Value	Type
Account Description	AirCatch Mail Server Settings	Description
Account Type	POP	Fixed
User Display Name	AirCatch Mail Server	Description
Email Address	iPad@mail.local	Description
Incoming Mail. These settings are used to prevent the iPad displaying messages that it cannot connect to a mail server. AirCatch will respond to requests to prevent errors, but will not deliver email		
Mail Server	Domain Name or IP address of AirCatch server	
Port	8105	Set in Configurator
User Name	AirCatch	Fixed
Authentication Type	Password	Fixed
Use SSL	false	Fixed
Password	A1r#POP3	Fixed
Outgoing Mail		
Mail Server	Domain Name or IP address of AirCatch server	
Port	25	Set in Configurator
User Name	bank	Fixed
Authentication Type	None	Fixed
Password	blank	Fixed
Use SSL	false	Fixed



AirCatch can automatically deploy contacts to the iPads, based on the monitored folder structure. To enable this, the following settings are required for Contacts

Key	Value	Type
Account Description	AirCatch Contacts	Description
Account Hostname	Domain Name or IP address of AirCatch server	
Port	8110	Set in Configurator
Principal URL	blank	Fixed
Account User Name	AirCatch	Set in Configurator
Password	A1r#DAV	Set in Configurator
Use SSL	false	Fixed